

# ELECTRONIC AUTOLOCK

Extreme MicroCoil® Grille – 500K Cycles & Extreme® 300 Series Grille

## AUTOMATIC LOCKING PROTECTION



Electronic AutoLock is available as standard for the Extreme MicroCoil® Grille, or as an option for the Extreme® 300 Series Grille. It can be retrofit to upgrade an existing high performance grille in the field. This guide mounted electronic lock provides additional security without compromising the grille's aesthetics, headroom or performance qualities. The Electronic AutoLock works by automatically engaging the cylinder lock when in the closed position, which is a great option for applications that want 24/7 security without 24/7 monitoring.

To keep the aesthetic appeal, this autolock is compact, with less than an inch of projection past the guide.

Lock Cylinder	Guide Material	Projection Past Guide Face
Best Cylinder Tapered	Aluminum	1/2"
	SST	15/16"

## ADDITIONAL FEATURES & SPECIFICATIONS

- For new orders, Electronic AutoLocks are preinstalled and mounted to the guides for easy adjustment in the field. For retrofit orders, guide replacement is required.
- Designed with a durable stainless steel cover and housing with a solenoid plate within the housing. The solenoid plate controls the state of the lock and is powered by the controller.
- The Electronic AutoLock is fail secure - during a power outage the locks will stay locked when the grille is in the closed position, but can be overridden with a key.
- Available for use with an Extreme MicroCoil Grille that has a max coil height of 14'5" and a max width of 26'1".
- Available for use with Extreme 300 Series Grille that has a max coil height of 16'4" and a max width of 30'4".

## PROVEN SECURITY

The Electronic AutoLock increases the overall security and strength of the Extreme MicroCoil Grille and 300 Series Grille by increasing lift resistance. Our high performance grilles in combination with the AutoLock system were tested for lift resistance with two assailants. The locks were able to withstand up to 1200 pounds of force on grilles with Aluminum guides and up to 940 pounds of force on Stainless Steel guides without the bottom bar lifting over the lock.



\*The lift resistance testing was performed on a 9' x 4' grille.